

WATERPROOF DOWNLIGHTS

Large recessed ceiling LED downlight with symmetrical light distribution on a wide beam and a high degree of protection. A sanded glass diffuser ensures a uniform light distribution. Extremely functional and weather resistant, Luisella is an ideal solution for general lighting applications also in interiors. Luisella is available on 3 different sizes. Low installation depth required. Round frame.

DIMENSIONS:

Ø 150 mm / 6.0 in (diameter) 38 mm / 1.50 in (height) Ø 112 mm / 4.41 in (recessed hole)


NET WEIGHT: 0.580 Kg. / 1.28 Lbs.

MATERIALS:

Body: POLICARBONATE Frame: AISI 316L Stainless Steel Protective glass (SANDED GLASS)

Note: Driver not included. CSL


























* Lumen & Lux Flow Data Relative to CSL Version LED CRI 80 / 3000 K

LUMEN 756



Lux 441 @ 1 мт.



BEAM 79° AMPLITUDE:



Model Specifics:

Model Code:	Watt:	Lumen:	Lm/W:	Beam:	CRI:
10LUISE05	10	756	84	79°	80

Variable product codes:

* ADD THE VARIABLE CODES TO THE ITEM MASTER CODE.

Power supply:

Code: N (VF 28 IF 350 - CSL) Code: D (24 v pc - CLL)

Color Temperature:

Code: 2 (2700 Kelvin) Code: 3 (3000 Kelvin) Finishes:

Code: SS (S/Steel AISI 316L) Code: LA (Lacquered RAL 9010)

