




ELECTRICAL PROPERTIES



		
POWER	2W	
SUPPLY	COSTANT VOLTAGE 8-32 VDC (DRIVER ON BOARD)	
PROTECTION	FUSE - POLARITY REVERSE SPIKE FILTER	
DIMMABLE	YES	
LIGHT SOURCE	OSRAM POWER LED	
LED COLOUR	3000K, 3000K+RED	




NEWPORT A85 3414/K2W-A85




MECHANICAL PROPERTIES

	
IP RATE	IP66
FIXTURE	ADJUSTABLE DOWNLIGHT FOR EXTERIOR/INTERIOR
FRAME	AISI 316L
HEATSINK	SPECIAL COMPOUND
SCREEN	OPAL
MOUNTING SYSTEM	SPRINGS

COLOUR	3000K	BEAM	90°
CRI	>80		
LUMEN OUTPUT	240 lm		
LIGHTNESS 1mt	111 lx		
LIGHTNESS 2mt	28 lx		
LIGHTNESS 3mt	12 lx		

FINISHES

POLISHED S.STEEL
BRUSHED S.STEEL
WHITE S.STEEL



CUT OUT	73mm (2.87in)
FRAME	85 mm (3.35in)
DEPTH	31mm (1.22in)
REFLECTOR ADJUSTABILITY	15° x 2