QT | OO Exchangeable Thru Hull

The QT100 LED underwater light features exchangeable inserts. This allows servicing and upgrades without the hassle of hauling your boat. With 10,000 lumens of light power and it's 90° degree beam angle the QT-100 LED is recommended for boats over 65' feet, installing each fixture 3 - 9 feet apart for the best illumination.

The QT100 is designed with an industry standard 72mm - 2 7/8" hole cutout facilitating an easy upgrade exchange from competitor fixtures. This housing design has been in production for 25 years with zero failures. Built with anodized aluminium and armor coated AB2 bronze. Supplied with an IP68 juntion box for seamless installation.

















Maintenance inside the hull



Hull Material GRP / Fiberglass



Boat Size 65+ feet



Hole Cut Out 2 7/8" / 72mm



10,000



Kelvin 6,500 1111

Beam Angle 90° degree











Installation Thru Hull

QT I 00

Exchangeable Thru-Hull

Mounting

Hull Material	GRP / Fiberglass
Boat Size	65+ Feet (20+m)
Spacing	3' - 9' (0.91 - 2.7m)
Beam Angle	90°
Installation Angles	Flush

Technical	Per Fixture
Lumens - max on single color	10,000
Kelvin - white light only	6,500
Typical LED Life Expectancy	40,000 hrs
Min-Max Operating Voltage	White = 12 - 24vDC Blue = 24vDC Color Change = 24vDC
Current / Amp draw	White = 6.8 - 3.2 amp Blue/ = n/a Color Change = 2.8 amps max on 4 channels
Driver Type	White = Internal Blue / Color Change = External
Driver Output	White = 36V DC - 1.9A Blue = 53V DC - 1.3A Color Change = 4 channels @ 0.7A
Control Options	White/ Blue = On / Off Switch Color Change = DMX
Bonding	Locking Ring
Physical	Per Fixture
Max Hull Thickness	3/64" (80mm)
Length of Fixture	5" (125mm)

Physical	Per Fixture
Max Hull Thickness	3/64" (80mm)
Length of Fixture	5" (125mm)
Diameter of Fixture	4" (100mm)
Profile (height) of Fixture	3/16" (5mm)
Removal Space Required	6 11/16" (170mm)
Total Weight	10lbs
Color Change and Blue Driver Dimensions (L x W x H)	7 3/32" x 4 3/4" x 3 1/2" (180 x 120 x 90mm)
Cable Length	White / Blue = 5' (1.5M) Color Change = 10' (3M)
Hole Cut-out	2 7/8" (72mm)
Material	Armor Coated AB2 Bronze
Growth Resistant Lens	Borosilicate Glass

Color Change and Blue Color Driver







Color		Part Numbe
White	0	QT100W
Blue		QT100B
RGBW		QT100RGBW





Underwater Lights Limited

UK Design and Production

The Great Dunton Forge, London Road, Dunton Green, Sevenoaks, Kent, TN13 2TD UK. T: +44 (0) 1732 455753 • F: +44 (0) 1732 743233

USA Sales Office

2830 W State Rd 84, Suite 107 Fort lauderdale, Florida, 33312, USA. T:+1 954 604 4024

E: uwl@underwaterlights.com